

## **AUTHORIZATION TO MARK**

This authorizes the application of the Certification Marks shown below to the Product Covered (also to the multiple listee model identified on the correlation page of the Listing Report where applicable) when made in accordance with the Description and under the conditions set forth in the Certification Agreement and Listing Report:

Applicant:

F.M.B. S.p.A

Via Turati, 16 – 40010 Sala Bolognese (BO) - Italy

Contact:

Name:

Mr. Luca Rappini

Phone:

+39 051 6814189

Manufacturer:

FIRBIMATIC S.p.A.

Via Turati, 16

40010 Sala Bolognese (BO) - Italy

Party Authorized To Apply Mark:

Same as Manufacturer

**Report Issuing Office:** 

INTERTEK Campoformido (Udine), ITALY

Report No.:

I0412020

**Product Covered:** 

Dry-Cleaning Equipment, models: HC7-15-CS, HC7-15-CL, HC7-18-CS, HC7-18-CL, HC7-18-CLM, HC8-18-CS, HC8-18-CL, HC7-20-CL, HC8-20-CS, HC8-20-CL,

HC7-25-CL, HC7-25-CLM, HC8-25-CS, HC8-25-CL, HC8-25-CLM, HC7-32-CL,

HC8-32-CL, HC7-40-CL, HC7-40-CLM, HC8-40-CL, HC8-40-CLM

**Description:** 

The products covered by this report are self-standing, closed circuit, stationary drycleaning machines with a suspended drum, provided with field wiring terminals, intended for cleaning items made from natural fibers, chemical fibers, artificial fibers, skins and furs. The suspended drum avoids vibrations to be transmitted to the machine or building structure and higher drying speeds are possible. The dry-cleaning machines use Class IIIA hydrocarbon solvent and Class IIIA silicon based solvent (decamethylpentacyclosiloxane)

Solvents have a flashpoint at or above 60°C (140°F) and below 93.4°C (200°F).

During the cleaning cycle, the solvent is kept at a temperature below 40°C (104°F), and therefore below the flashpoint, by a refrigeration unit. The solvent then remains at

atmospheric temperature during the extract phase.

Standard(s):

Commercial Dry-Cleaning Machines (UL 664, 4th Edition 1993)

Commercial Laundry and Dry-Cleaning Operations (ANSI Z8.1, 1996)

Canadian Electrical Code (CAN/CSA -C22.2 No. 0 -M91)

Standard for Drycleaning Plants (NFPA 32, 2000)

This document is the property of Intertek Testing Services and is not transferable. Only the Applicant may reproduce this document. The certification mark(s) may be applied only at the above noted location of the Party Authorized To Apply Mark.

Authorized by:

Jonas Backstad for

William T. Starr, Certification Manager

Control Number:

3062757

Intertek Testing Services NA Inc. 165 Main Street, Cortland, NY 13045 Telephone 800-345-3851 or 607-753-6711 Fax 607-756-6699 Page 15

Issued: April 20, 2004

## **CORRELATION PAGE FOR MULTIPLE LISTINGS**

The following products, which are identical to those identified in the Product Description except for model number and Listee name, are authorized to bear the ETL label under provisions of the INTERTEK Multiple Listing Program.

## **MULTIPLE LISTING**

The following products which are identical to those identified in the index except for model number and participant name are authorized to bear the ETL label under provisions of the INTERTEK Multiple Listing Program

**MULTIPLE LISTEE** 

FIRBIMATIC S.p.A.

Via Turati, 16 – 40010 Sala Bolognese (BO) - Italy

**BASIC LISTEE** 

F.M.B. S.p.A

Via Turati, 16 – 40010 Sala Bolognese (BO) - Italy

**MANUFACTURERS** 

FIRBIMATIC S.p.A.

Via Turati, 16

40010 Sala Bolognese (BO) - Italy

RO		

## **Dry-Cleaning Equipment**

MULTIPLE LISTEE MODEL NO.	BASIC LISTEE MODEL NO.
ECOPRO 915S/35 ECOPRO 915/35 ECOPRO 918S/40 ECOPRO 918/40 ECOPRO AM918/40 S2118 L2118 ECOPRO 920/50 S2120 L2120 ECOPRO 925/60 ECOPRO AM925/60 S2125 L2125 AM2125 ECOPRO 932/80 L2132 ECOPRO 940/95 ECOPRO AM940/95 L2140	HC7-15-CS HC7-15-CL HC7-18-CS HC7-18-CL HC7-18-CLM HC8-18-CS HC8-18-CL HC7-20-CL HC8-20-CS HC8-20-CL HC7-25-CL HC7-25-CL HC7-25-CLM HC8-25-CS HC8-25-CL HC8-25-CL HC8-25-CL HC8-32-CL HC7-32-CL HC7-40-CL HC7-40-CLM HC8-40-CL
AM2140	HC8-40-CLM